

NOTE:


1) THREAD DETAILS. BASIC ISO 68-1:1998 THREAD PROFILE WITH A 6H **TOLERANCE CLASS IN** ACCORDANCE WITH ISO 965-1:2013 2) MARKING TO BE IN

THE MIDDLE OF COUPLER MARKING:

LINE 1 WORT COUPLER TYPE



| Item | Article No. | Rebar | Length | OD | Thread |
|------|-----------------|-------|--------|-----|-------------|
| 1 | 101-03MM-XX0018 | 12 | 36 | Ø28 | M13 x P1.75 |
| 2 | 101-03MM-XX0012 | 16 | 36 | Ø30 | M17 x P2.5 |
| 3 | 101-03MM-XX0013 | 20 | 41 | Ø32 | M21 x P2.5 |
| 4 | 101-03MM-XX0014 | 25 | 48 | Ø40 | M26 x P3.5 |
| 5 | 101-03MM-XX0015 | 28 | 53 | Ø45 | M29 x P3.5 |
| 6 | 101-03MM-XX0016 | 32 | 60 | Ø50 | M33 x P3.5 |
| 7 | 101-03MM-XX0017 | 36 | 65 | Ø55 | M37 x P3.5 |



a) The property of Halfen Moment S/B,b) Confidential

O) May also be legally privileged.
They are intended for the person attention to. Any person other the attention shall not disclose, copy or distribute in reliance on them.
Any technical advice/support or drawings provided by us in whatever form is given to the best of our knowledge and for genera



| drawings provided by us in whatever form is given to the best of our knowledge and for general use only and shall be considered non-binding information. | | | | | | | | | | |
|--|-----------|-------------|--------|----------|-------------|----------|-------------|---------------------|--|--|
| | Material | | | | | | | Article Name | | |
| | Alternate | | | | | | | Coupler Weldable RT | | |
| • | Material | | | | | | | (Customer Drawing) | | |
| | Finish | | | 19/03/20 | | | | (| | |
| | Tolerance | | Rev No | Date | Description | Drawn by | Approved by | Article Number | | |
| | | Refer Table | | | | | | | | |